

Inkjet Media for Screen Printing

Product Description	4 or 5mil Clear Polyester Film, Inkjet Printable
Short Roll Sizes	17 in., 24 in., 36 in., 42 in. x 100 ft.
No Interleaf Paper	Custom roll sizes by request
Sheet Sizes	8.5 in. x 11 in., 8.5 in. x 14 in., 11 in. x 17 in., 13 in. x 18 in., 13 in. x 19 in., 17 in. x 22 in.
With Interleaf Paper	Custom sheet sizes by request
Application	Film Positive to burn silk screens

Media Features

- No Need for Cameras or Processors
- High Ink Densities
- Fine-line Detail
- Compatible with Piezo-type, Small and Large Format Inkjet Printers
- Quick Drying Time
- Heat Resistant
- Dimensionally Stable

Structure

Recommended Handling and Storage Conditions

Clear Inkjet Layer	Temperature	Relative Humidity
Clear Polyester Film	Handling 65-85°F (18-27°C)	20 – 60% non-condensing
Anti-Curl or Anti-static Layer	Storage 50-90°F (10-30°C)	20 – 80% non-condensing
Unprinted Media	Store the unprinted media in its original plastic sleeve to protect the sheets from degradation and damage.	

Physical Properties

Silkjet Types	SC4	UC5
Total Caliper	110 µm / 4.2 mil	140 µm / 5.5 mil
Basis Weight	105 g/m ²	175 g/m ²
% Haze	4	6
% Gloss at 60°	128	117
Shelf Life (date of manufacture)	One year	One year
% Light Transmittance	93	93
Water Fastness	No	No
Ink Compatibility	Dye only	Dye and Pigment
UV Density of Background	0.06	0.10
UV Density Image (E3000)	3.04	4.0
UV Density Image (E4000)	N/A	4.0
Grade	Economical	Standard
Appearance	Clear	Clear

Warranty Information: Silkjet media are warranted to be free from defects in materials and manufacture.

Disclaimer: The data represented in this document is for reference only and should be regarded as a guideline for use. Please make sure that our media is suitable for the printer and the intended application.