



Ultrafix PT

APPLICATIONS

Holds garments securely on pallet, or belt, during printing.

GENERAL CHARACTERISTICS

- Water-based pressure-sensitive adhesive
- High tack level holds fleece & tees
- Flash safe & non-staining
- Non-flammable & no VOC's
- Resists breakdown when printing with water based or discharge inks

DIRECTIONS FOR USE

Apply directly onto pallet or on top of pallet protecting tape. Spread a thin layer with brush, roller, card or squeegee and allow to dry before use. Can also be spray-applied using pneumatic or electric-operated spray gun. Can be reapplied, or tack can be reactivated by wiping with sponge and warm water to remove lint build-up. Remove old adhesive by cleaning with Remove IR ink degrader, or other suitable solvent.

HEALTH & SAFETY

Before using, refer to appropriate material safety data sheets.

STORAGE

When sealed in the original container and stored in cool conditions, SaatiChem products will maintain their original properties for two years from the date of production.

PACKAGING

Available in 8 oz, 1 qt, 1 US gallon, 5 US gallon and 55 US gallon containers.

WARRANTY & LIMITED REMEDY

The directions recommendations, and specifications contained in this Technical Data Sheet are meant as a guide to the use of the product and shall not bind the company. Product specifications are subject to change without notice.

The following is made in lieu of all other expressed or implied warranties, including any implied warranty of merchantability or fitness for a particular purpose:

All SaatiChem manufactured liquid products are warranted to be free of defects in materials and manufacture and to meet the specifications stated in SaatiChem's applicable Product Bulletin. SaatiChem will replace or refund the price of any SaatiChem manufactured liquid product that does not meet this warranty within the applicable warranty period.

The remedies are exclusive. In no case shall SaatiChem be liable for any other direct or indirect damage or loss, including without limitation any incidental, special, or consequential damages, or any material costs or labor charges incident to the removal or replacement of any mesh, screen, ink, substrate, finished graphic or any other item.

To receive the Material Safety Data Sheet (MSDS), send an e-mail to: MSDS@saatichem.com

USA
1.877.296.7697 (Toll-free US &
Canada or 1.847.296.7697
E-mail: info.US@saatichem.com

Italy
+39.031.9711
E-mail: info.IT@saatichem.com

China
+86.21.58999113
or +86.21.58339020
E-mail: info.CN@saatichem.com

For More Information
about SaatiChem
visit our website:
www.saatiamericas.com